

Technical Data Sheet

NEOPOR® ThermaPlus™ WRB Plus CI + AB

Made with BASF Neopor® GPS – For Use on
Above Grade Exterior Walls

Exclusively using BASF Neopor® GPS (Graphite Polystyrene) rigid foam in conjunction with Barricade® Wrap Plus WRB is today's energy-efficient and cost-effective insulation solution. The combination of both products creates NEOPOR® ThermaPlus™ which can be used to insulate the exterior of your building, creating a complete envelope to help eliminate thermal bridging and reduce air infiltration.

Meet Codes with NEOPOR® ThermaPlus™

- Complies with the 2015, 2018, and 2021 International Energy Codes
- Building Code Compliance - ICC ESR 4431
- Meets ASTM C 578

NEOPOR® ThermaPlus™ Test Results

Test	Method	Results
Water Penetration	ICC ES AC 71 section 3.4	Pass
Weathering	ICC ES AC 71 section 3.5	Pass
Water resistance	ICC ES AC 71 section 3.1.4	Pass
Density	ASTM D 1622	1.35 pcf minimum
Compressive Strength	ASTM D 1621	➤ 15 PSI
Flexural Strength	ASTM C 203	➤ 35 PSI
Water Vapor Transmission	ASTM E 96 method	Qualify as a Class III vapor retarder
Air Permeance	ASTM E 283	Air impermeable
Surface Burning Characteristics	ASTM E 84/ UL 723	Less than 25 flame and 450 smoke development indexes
Thermal Insulation Value	ASTM C518	R5 – 1" thick at 40 F and 1 1/16" thick at 75° F R10 – 2" thick at 40 F and 2 1/8" thick at 75° F

NEOPOR® ThermaPlus™ Material Properties

ASTM C578-19 ¹	Type II
Compressive Resistance @10% def., Min. PSI	15
Flexural Strength Resistance Min., PSI	35
Water Vapor Permeance Max., perms	>1.0
Water Absorption Max., %	1.1
Dimensional Stability Max., %	2

¹ Unless noted otherwise, properties are based on 1" thickness without laminate.

² Based on an independent testing laboratory. Water vapor permeance properties tested without laminate and 1.0" thick Neopor®



Installation Basics:

1. Proper storage, handling, and installation of NEOPOR® ThermaPlus™ is necessary to alleviate product damage.
2. NEOPOR® ThermaPlus™ can be installed vertically or horizontally over many properly prepared substrates including framing, sheathing, concrete and CMU. All edges of NEOPOR® ThermaPlus™ shall be supported by blocking, framing, sheathing or solid substrates.
3. Tightly abut adjoining sheets of NEOPOR® ThermaPlus™ and fit around openings, penetrations, etc. Secure with appropriate type, length and spaced fasteners based on substrate type, NEOPOR® ThermaPlus™ thickness, etc. And as described in NEOPOR® ThermaPlus™ Installation Guidelines.
4. Apply Construction Seam Tape per manufacturer's instructions across vertical, horizontal and other seams of adjacent sheets and pieces of NEOPOR® ThermaPlus™.
5. Flash and seal fenestrations, penetrations and openings with Flashing Tape installed per manufacturer's instructions or with other compatible materials that meet design and building code requirements.
6. Confirm proper installation of NEOPOR® ThermaPlus™, Construction Seam Tape, and flashings prior to installation of exterior wall covering.
7. Refer to Installation Guidelines and website (www.neopor-insulation.com) for complete NEOPOR® ThermaPlus™ application information.

Meet Sustainability Goals with NEOPOR® ThermaPlus™

- Available in R-5 or R-10 – Minimizes thermal bridging and helps cavity insulation perform better
- 15 psi Compressive Strength – Meets jobsite durability requirements without overuse of raw materials
- Excellent long-term thermal resistance (LTTR) – HFC free and provides stable R value over time
- Vapor Permeable – allows for design flexibility and increased building durability and resiliency
- Zero ozone-depletion potential and UL GREENGUARD Gold certified for air quality

Product Protection:

Prolonged direct sunlight exposure or reflected sunlight can adversely affect Neopor® board insulation. Keep insulation inside protective packaging during storage, transportation and job site usage. Please refer to the Neopor® Handling Instructions.

Availability and Warranty:

Warrantied and supplied across North America from BASF NEOPOR® authorized manufacturers listed under ICC ESR 4431 or visit our website www.Neopor-Insulation.com

Tested, Trusted, True



THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH, AND ARE BASED ON BASF'S CURRENT KNOWLEDGE AND EXPERIENCE. THEY ARE PROVIDED FOR GUIDANCE ONLY, AND DO NOT CONSTITUTE THE AGREED CONTRACTUAL QUALITY OF THE PRODUCT OR A PART OF BASF'S TERMS AND CONDITIONS OF SALE. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE OF THE PRODUCT, BASF RECOMMENDS THAT THE READER CARRY OUT ITS OWN INVESTIGATIONS AND TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR ITS PARTICULAR PURPOSE PRIOR TO USE. IT IS THE RESPONSIBILITY OF THE RECIPIENT OF PRODUCT TO ENSURE THAT ANY PROPRIETARY RIGHTS AND EXISTING LAWS AND LEGISLATION ARE OBSERVED. **NO WARRANTIES OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH HEREIN, OR THAT THE PRODUCTS, DESCRIPTIONS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS.** ANY DESCRIPTIONS, DESIGNS, DATA AND INFORMATION GIVEN IN THIS PUBLICATION MAY CHANGE WITHOUT PRIOR INFORMATION. THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY BASF HEREUNDER ARE GIVEN GRATIS AND BASF ASSUMES NO OBLIGATION OR LIABILITY FOR THE DESCRIPTIONS, DESIGNS, DATA OR INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT THE READER'S RISK

BASF Corporation, 2021.

® = Registered trademark of the BASF Group.